



Continental Materials, Inc.

Jenkintown Plaza • 101 Greenwood Ave. • Jenkintown, PA 19046

(215) 884-4930 • Fax (215) 887-4485 • (800) 247-6637

www.continentalmaterials.com

No. 15 Asphalt Felt - Regular (RF890)

Description

Saturated felt is a uniform, flexible felt of organic fibers, impregnated with an asphalt saturant. Line markings are placed on the top surface at 2", 8 1/2", 11 5/16", and 17" from each side of the sheet.

Uses

A roofing felt used as an underlayment beneath asphalt shingles, wood shakes, tiles and other sloped roof coverings.

Physical Properties

Width of roll	3 ft.
Length of roll	144 ft.
Contents	432 sq. ft.
Weight per roll (approx.)	34 lbs
Rolls per pallet	39
Pallets per truck	34
Rolls per truck	1,326

Storage: Always store rolls upright on pallets and in a dry protected area.

Characteristics	Test Method	Typical
Net mass per unit area of saturated felt lb/100 sq. ft.	ASTM D-146	7.8
Mass of saturant lb/100 sq. ft.	ASTM D-146	3.9
Mass of de-saturated felt, min lb/100 sq. ft.	ASTM D-146	3.9
Saturant in moisture free felt, by mass (% avg.)	ASTM D-146	95% min
Pliability at 25° c	ASTM D-146	PASS