



CONTINENTAL MATERIALS, INC

Fasteners • Asphalt • Underlayments • Fiberboard • Tools

*"Quality Manufactured  
Components...  
Making Construction  
Systems Perform Better  
Since 1958"*

# Asphalt Roofing Felts

Underlayments

*"Top Quality  
Roofing Felts  
At Prices You  
Can Afford!"*

- **Best Value...** Affordable price with superior quality
- **Highest Quality Asphalt...** Unlike most manufacturers, we process our own asphalt to ensure highest quality and consistency
- **Environmentally-Friendly Organic Core...** Made in our own plants from 100% reclaimed/recycled material with a minimum of 10% post-consumer content (paper)
- **Consistent Saturation...** For superior moisture resistance and code compliance
- **Versatile...** Can be used under fiberglass shingles, wood shakes, tile, and other sloped roof coverings
- **Clearly Marked Guidelines...** for easy installation
- **Nationwide Manufacturing...** for more consistent supply and ready availability



visit us at [www.continentalmaterials.com](http://www.continentalmaterials.com)

# Asphalt Roofing Felts

"Top Quality Roofing Felts At Prices You Can Afford"



## Description

CMI saturated felt is a uniform, flexible felt of organic fibers, impregnated with an asphalt saturant. Line markings are placed on the top surface for ease of installation.

## Uses

A roofing felt used as an underlayment beneath fiberglass and asphalt shingles, wood shakes, tiles, and other sloped roof coverings. It helps to stop leaks caused by wind-driven rain.

## Storage

Always store rolls upright on pallets and in a dry protected area.

## Availability

Not all felt types are available in all areas. Other asphalt roll roofing products (43# coated base sheet and mineral surface roll roofing) available in some areas. Check with your CMI representative for availability.

Physical Properties						
	No. 15 Regular	No. 15 ASTM D4869 Type I	No. 15 ASTM D226 Type I	No. 30 Regular	No. 30 ASTM D4869 Type II	No. 30 ASTM D226 Type II
Width	36"	36"	36"	36"	36"	36"
Length	144'	144'	144'	72'	72'	72'
Sq. Feet / Roll	432 ft <sup>2</sup>	432 ft <sup>2</sup>	432 ft <sup>2</sup>	216 ft <sup>2</sup>	216 ft <sup>2</sup>	216 ft <sup>2</sup>

Specifications (meets or exceeds applicable requirements)						
	No. 15 Regular	No. 15 ASTM D4869 Type I	No. 15 ASTM D226 Type I	No. 30 Regular	No. 30 ASTM D4869 Type II	No. 30 ASTM D226 Type II
Net mass per unit area of saturated felt lbs/100 sq ft	7.8	8.0	11.5	15.3	21.6	26.2
Mass of saturant min lbs/100 sq ft	3.9	4.0	6.2	8.3	12.6	15.0
Mass of de-saturated felt, min lbs/100 sq ft	3.9	4.0	5.2	6.7	9.0	10.0
Saturant in moisture free felt, by mass (% avg)	95% min	100% min	120% min	120% min	140% min	150% min
Pliability at 25C	Pass	Pass	Pass	Pass	Pass	Pass




**"Quality Manufactured Components... Making Construction Systems Perform Better Since 1958"**

## No-Smell™ Asphalt



Virtually eliminates objectionable asphalt odors during the installation—so complaints from occupants and the neighbors disappear.

## Fiberboard



Your best choice for reliable performance in asphaltic or single ply roofing systems. It's even environmentally-friendly!

## Underlayments



Top quality synthetic and asphaltic underlayments at prices you can afford—and with quality that you can rely on every day.

## Fasteners



Superior value has made us one of the largest and fastest-growing fastener suppliers in North America—for more than half a century!

## Application Tools



Ultra-high purity, 100% cotton mops deliver long-lasting performance and the perfect balance between cost and service life.