



# SecureGrip MTS Premium Synthetic Roof Underlayment

**Extreme Performance**  
for a Superior Roof System

*"Extreme Performance Roof Deck Protection – Under Metal, Tile, Slate, and Premium Asphalt Shingle Roofs!"*

- **Highly Engineered...**extremely strong woven polypropylene fabric with U.V. and water resistive coatings that adds water-shedding redundancy in the roofing system while protecting the structure from damage.
- **100% Inorganic...**synthetic construction offers long term moisture protection - doesn't absorb water, won't rot and is inert to mold growth.
- **Advanced Design Surface Technologies...**SecureWalk™ (top) and SecureGrip (back) create extreme walkability.
- **Improves Project Outcome...**rolls out flat and does not wrinkle causing customer callbacks.
- **Easier Installation...**33% more coverage per pass across the roof (vs. 36" wide rolls) - with anti-slip engineered back and walking surfaces for great traction.
- **Superior Performance...**designed to perform in virtually all steep slope roofcovering systems and in extreme weather conditions.
- **Durable...**heavy synthetic construction resists tearing during roof installation - UV stabilized to resist UV degradation up to 6 months.

### Description

CMI SecureGrip MTS Synthetic Roof Underlayment is a synthetic roof-deck protection designed and manufactured to replace asphalt saturated 30# felt in sloped roof system construction where toughness and longer exposures may be required.

### Uses

A superior performing roofing underlayment used beneath metal, tile, slate as well as under fiberglass and asphalt and metal shingles and shakes.

### Storage

Always store rolls upright on pallets (or in the cradled pallet they are shipped on) and in a dry protected area.

### Availability

SecureGrip Synthetic Underlayments are available throughout the United States. Check with your local representative for product availability.



### SPECIFICATIONS (meets or exceeds applicable standards)

	Standard	SecureGrip MTS
<b>Mech Attached Polymer UDL</b>	ASTM D 8257	pass
<b>Permeability</b>	ASTM E96	< .03 perms
<b>Water Transmission</b>	ASTM D4869	pass
<b>Nail Sealability</b>	ASTM D1970	pass
<b>Pliability</b>	ASTM D226	pass
<b>Tear Strength</b>	ASTM D4533	MD75 lbs / CD 72 lbs
<b>Tensile Strength</b>	ASTM D751	MD 253 lbs / CD 241 lbs
<b>Wt Per Square</b>	ASTM D5261	3.9 lbs
<b>Nominal Thickness</b>	ASTM D5261	20 mils
<b>Range of Temperature</b>		- 40°F to 240°F
<b>Fire Rating UL Class A</b>	ASTM E108	pass

### COMPLIANCE: CODES

Performance characteristics meet or exceed ASTM D4869 – Type I, II, III and IV

Performance characteristics meet or exceed ASTM D226 – Type I, II

Tested in accordance with ICC-AC-207- UV Exposure – 180 days

U.L. Classified as a Prepared Roofing Accessory

Meets the requirements of ICC-AC-188 – Intertek / WH

FBC Approved – #FL46488

TDI Listed – CCRR #0439

Miami-Dade County approved

### PHYSICAL INFORMATION

<b>Per Roll</b>	48" X 250'	<b>Rolls Per Pallet</b>	25
<b>Material Per Roll</b>	1000 sq. ft.	<b>Wt Per Pallet</b>	1,174 lbs
<b>Squares Per Roll</b>	10 squares	<b>Wt Per 100 sq. ft.</b>	3.9 lbs
<b>Weight Per Roll</b>	40 lbs	<b>Limited Warranty</b>	Lifetime



@cmi1958



Intertek