

## HIGH PERFORMANCE SELF ADHESIVE ROOFING SHINGLE STARTER

### DESCRIPTION

**CMI SecureGrip Shingle Starter SA** is a mineral surfaced self-adhesive membrane product made with a flexible polymer-modified bitumen compound and reinforced with a tough glass fiber mat substrate. The starter roll has a self-adhering strip on the top surface to promote wind uplift resistance..

**CMI SecureGrip Shingle Starter SA** peel and stick application allows fast installation, saving time and labor. The membrane is waterproof and self-sealing around nails. The starter roll may be adhered directly to the roof deck or to SecureGrip self-adhering underlayment.

### USES

**SecureGrip Shingle Roll Starter PS** is used to reduce the chance of shingle blow-off at the eaves and rakes. It provides waterproofing at eave and rake edges during roofing or re-roof process

### STORAGE

The product must be stored in the original and unopened packaging in a dry and well-ventilated place at a temperature between 40°F and 105°F. Storage above 120°F may lead to difficulty in removing the release liner when applying.

### AVAILABILITY

**CMI SecureGrip Shingle Starter SA** is available throughout the United States. Check with your local representative for product availability.

### TECHNICAL PARAMETERS

PHYSICAL PROPERTIES	METHOD	VALUE
Nail Sealability	ASTM D1970	Pass
Thickness		48 mils
Tensile Strength	ASTM D1970	28 lbf/in / 25 lbf/in
Tear Resistance	ASTM D1970	21 lbf / 21 lbf
Elongation at Break	ASTM D1970	10 %
Adhesion to Plywood @ 40°F, min	ASTM D1970	6 lbf/ft
Adhesion to Plywood @ 75°F, min	ASTM D1970	16 lbf/ft
Waterproof integrity of lap seam	ASTM D1970	Pass
Slip Resistance	ASTM D1970	0.9 N/mm2
Waterproof integrity after low temp flex	ASTM D1970	Pass

### FEATURES

**Self-Adhesive Starter Roll:** Premium roll with durable mineral surface for long-lasting performance.

**User-Friendly Design:** Silicone release film backing ensures easy handling and placement.

**Built-In Sealant Strip:** Modified asphalt strip on the top surface delivers strong, lasting adhesion.

**Quick & Easy Installation:** Peel-and-stick application allows for less cutting, tools, and fasteners.

**Time-Saving Solution:** Eliminates the need for traditional starter shingles, reducing labor.

**Long-Term Bonding:** Sealant strip maintains adhesion strength over time for reliable roof performance.

**Enhanced Nail Sealability:** Advanced compound formulation seals tightly around nails for added protection.

### PACKAGING

Standard Width	7.2"
Standard Length	33'
Rolls / Box	6
Boxes / Pallet	30 boxes
Rolls / Pallet	180 rolls
Roll Weight	7.1 lbs (3.2 kg)
Pallet Weight	1325 lbs (601 kg)

### CODE APPROVALS & STANDARDS

Product meets or exceeds the physical requirements of ASTM D1970

### SURFACE PREPARATION

The starter roll must be applied to a clean, dry, smooth and dust-free surface. No special tools are required to install this self-adhering roll starter.



Product qualified for use as a component of a FORTIFIED Roof™. Additional requirements, eligibility criteria and restrictions apply. For details, visit [FORTIFIEDHome.org](http://FORTIFIEDHome.org).



**Asphalt Roofing  
Manufacturers Association**