



SECUREGRIP™

XTRA ROOF DECK SEAM TAPE

HIGH PERFORMANCE BITUMEN ROOF DECK SEAM TAPE WITH POLY-SURFACE

DESCRIPTION

SecureGrip™ XTRA Roof Deck Seam Tape is a premium grade self adhering roof deck seam tape with a slip resistant surface. It is manufactured with a flexible polymer modified bitumen compound laminated onto a non-woven polyester providing a walkable surface. The adhesive side is protected with a release film which is removed before application.

USES

SecureGrip™ XTRA Roof Deck Seam Tape applies to seams of plywood or OSB roof decking. It provides an additional layer of self-adhering protection against damaging water intrusion at roof deck joints. **SecureGrip™ XTRA Roof Deck Seam Tape** is easy to use on the deck as well as in small areas.

STORAGE

The product must be stored in the original and unopened packaging in a dry and well-ventilated area at a temperature between 40°F and + 40°C. Storage above 100°F may lead to difficulties in removing the release liner when applying.

AVAILABILITY

SecureGrip XTRA Roof Deck Seam Tape is available throughout the United States. Check with your local representative for product availability.

TECHNICAL PARAMETERS		
PHYSICAL PROPERTIES	METHOD	VALUE
Nail Sealability	ASTM D 1970	Pass
Thickness		40 mils
Tensile Strength	ASTM D 1970	25 lbf/in / 25 lbf/in
Tear Resistance	ASTM D 1970	21 lbf / 21 lbf
Elongation at Break	ASTM D 1970	10 %
Adhesion to Plywood @ 40°F, min	ASTM D 1970	6 lbf/ft
Adhesion to Plywood @ 75°F, min	ASTM D 1970	16 lbf/ft
Waterproof integrity of lap seam	ASTM D 1970	Pass
Slip Resistance	ASTM D 1970	0.9 N/mm2
Waterproof integrity after low temp	ASTM D 1970	Pass

FEATURES

Excellent Adhesion: Premium-grade adhesive formulation ensures strong, lasting bond.

Flexible Self-Adhering Membrane: Conforms easily to roof deck seams and irregular surfaces.

All-Temperature Performance: Maintains reliable adhesion from 40°F to 120°F.

Waterproof & Self-Sealing: Creates a watertight barrier that seals around fasteners.

Slip-Resistant Surface: Textured finish improves traction for safer handling and walkability

PACKAGING	
Standard Widths	4 inch
Standard Length	67 feet
Rolls Per Box	9 rolls
Approx Weight Per Roll	2.3 kg / 5.1lbs
Boxes Per Pallet	25 boxes
Rolls Per Pallet	225 rolls

CODE APPROVALS & STANDARDS

Meets or exceeds the physical requirements of ASTM D1970
 FBC Approved #44420
 Meets TDI Requirements

SURFACE PREPARATION

The tape must be applied to a clean, dry, smooth and dust-free surface. For an application in cold temperature, ensure that frost or condensation are absent on the surface. No special tools are required to install this sealing tape.



Product qualified for use as a component of a FORTIFIED Roof™. Additional requirements, eligibility criteria and restrictions apply. For details, visit FORTIFIEDHome.org.