



SECUREGRIP™

XTRA ROOF DECK SEAM TAPE

HIGH PERFORMANCE BITUMEN ROOF DECK SEAM TAPE WITH POLY-SURFACE

APPLICATION INSTRUCTIONS

DESCRIPTION

SecureGrip™ XTRA Roof Deck Seam Tape is a premium grade self-adhering roof deck seam tape with a slip resistant surface. It is manufactured with a flexible polymer modified bitumen compound laminated onto a non-woven polyester providing a walkable surface. The adhesive side is protected with a release film which is removed before application.

USES

SecureGrip™ XTRA Roof Deck Seam Tape applies to seams of plywood or OSB roof decking. It provides an additional layer of self-adhering protection against damaging water intrusion at roof deck joints. **SecureGrip™ XTRA Roof Deck Seam Tape** is easy to use on the deck as well as in small areas.

SURFACE PREPARATION

The tape must be applied to a clean, dry, smooth and dust-free surface. For an application in cold temperature, ensure that frost or condensation are absent on the surface. No special tools are required to install this sealing tape.

INSTALLATION INSTRUCTIONS

Unroll the tape until the desired length is reached. Start removing the release liner that covers the adhesive part of the tape and position the sealing tape. Work from the lowest point upward to ensure proper shingle-style overlap. Carry out a roll-pressing to avoid entrapment of air bubbles. When connecting two tapes, use an overlap of at least 2". Press with a roller or a cloth pad. Recommended application temperature is 40°F to 120°F (4°C to 50°C). Once the seams are taped, you may follow up to cover the roof with synthetic or self-adhering underlayments.

STORAGE

The quality and the characteristics of the materials remain unaltered for a long period of time. However, it is recommended to use the product within 12 months from production date. The product must be stored in the original and unopened packaging in a dry and well-ventilated place at a temperature between 40°F to 100°F (5°C to 40°C). Storage above 120°F (50°C) may lead to difficulties in removing the release liner when applying.