



SECUREGRIP™ SHINGLE STARTER SA

HIGH PERFORMANCE SELF ADHESIVE ROOFING SHINGLE STARTER

APPLICATION INSTRUCTIONS

DESCRIPTION

SecureGrip™ Shingle Starter SA is a 48-mil self-adhered membrane designed to simplify starter course installation by eliminating the need to cut shingle tabs. The mineral-surfaced top layer provides long-term durability, while the built-in sealant strip helps resist wind uplift along the roof edge. The peel-and-stick design promotes fast application and forms a fully bonded, waterproof starter layer. The membrane may be applied directly to the roof deck or over compatible self-adhered underlayments.

INSTALLATION INSTRUCTIONS

- Ensure the deck surface is clean, dry, and free of nails, dust, or debris.
- Recommended installation temperature is 40°F (4°C) and higher.
- If required for improved adhesion, apply a light coat of ASTM D41 asphalt primer and let it dry before proceeding with installation.

EAVE APPLICATION

1. Lay SecureGrip™ Shingle Starter SA parallel to the eave, granule side up, with the sealing strip closer to the roof edge.
2. Extend the membrane 1/4"–3/4" (6–19 mm) beyond the eave and rake edge. If the drip edge projects past the deck, align the membrane flush with the drip edge.
3. Remove the release film in sections, roll the membrane into position, and press uniformly by hand or roller to achieve a smooth, fully bonded surface.
4. Stagger end laps of adjacent rolls at least 4" (101.6 mm) from the butt joints of the first shingle course.

RAKE APPLICATION

1. Overlap the SecureGrip™ Shingle Starter SA over the eave starter course by at least 3" (76 mm).
2. Remove the release liner, roll the membrane in place, and apply even pressure to ensure wrinkle-free, full adhesion along the rake.

GENERAL INSTRUCTIONS

Install only as much material that will be shingled the same day to avoid contamination.
When starting a new roll, overlap the previous by a minimum of 6" (152 mm).

ADDITIONAL NOTES

In temperatures below 40°F (4°C), temporary spot-nailing may be needed until adhesion improves as the temperature increases. Confirm compatibility of all primers, caulks, and sealants before use.

STORAGE REQUIREMENTS

Store rolls upright in a cool, dry area, preferably in original packaging.
Protect from moisture, direct sunlight, and temperatures above 100°F (38°C).
Do not unwrap until ready for use; in cold conditions, warm rolls indoors prior to installation.

WARNINGS

Do **NOT** apply over uncured solvent-based sealants—active solvents can degrade the adhesive.
Do **NOT** use on PVC or silicone roofing substrates.
Roofing work carries inherent risks—follow all safety protocols and wear appropriate protective equipment.

