



SECUREGRIP™ SA STARTER ROLL

HIGH PERFORMANCE SELF ADHESIVE STARTER ROLL

DESCRIPTION

CMI SecureGrip SA Starter Roll is a mineral surfaced self-adhesive membrane product made with a flexible polymer-modified bitumen compound and reinforced with a tough glass fiber mat substrate. The starter roll has a self-adhering strip on the top surface to promote wind uplift resistance..

CMI SecureGrip SA Starter Roll peel and stick application allows fast installation, saving time and labor. The membrane is waterproof and self-sealing around nails. The starter roll may be adhered directly to the roof deck or to SecureGrip self-adhering underlayment.

USES

CMI SecureGrip SA Starter Roll is used to reduce the chance of shingle blow-off at the eaves and rakes. It provides waterproofing at eave and rake edges during roofing or re-roof process

STORAGE

The product must be stored in the original and unopened packaging in a dry and well-ventilated place at a temperature between 40°F and 105°F. Storage above 120°F may lead to difficulty in removing the release liner when applying.

AVAILABILITY

CMI SecureGrip SA Starter Roll is available throughout the United States. Check with your local representative for product availability.

TECHNICAL PARAMETERS

PHYSICAL PROPERTIES	METHOD	VALUE
Nail Sealability	ASTM D1970	Pass
Thickness		48 mils
Tensile Strength	ASTM D1970	28 lbf/in / 25 lbf/in
Tear Resistance	ASTM D1970	21 lbf / 21 lbf
Elongation at Break	ASTM D1970	10 %
Adhesion to Plywood @ 40°F, min	ASTM D1970	6 lbf/ft
Adhesion to Plywood @ 75°F, min	ASTM D1970	16 lbf/ft
Waterproof integrity of lap seam	ASTM D1970	Pass
Slip Resistance	ASTM D1970	0.9 N/mm2
Waterproof integrity after low temp flex	ASTM D1970	Pass

FEATURES

Self-Adhesive Starter Roll: Premium roll with durable mineral surface for long-lasting performance.

User-Friendly Design: Silicone release film backing ensures easy handling and placement.

Built-In Sealant Strip: Modified asphalt strip on the top surface delivers strong, lasting adhesion.

Quick & Easy Installation: Peel-and-stick application allows for less cutting, tools, and fasteners.

Long-Term Bonding: Sealant strip maintains adhesion strength over time for reliable roof performance.

Enhanced Nail Sealability: Advanced compound formulation seals tightly around nails for added protection.

PACKAGING

Standard Width	7.2"
Standard Length	33'
Rolls / Box	6
Boxes / Pallet	30 boxes
Rolls / Pallet	180 rolls
Roll Weight	7.1 lbs (3.2 kg)
Pallet Weight	1325 lbs (601 kg)

CODE APPROVALS & STANDARDS

Product meets or exceeds the physical requirements of ASTM D1970 and TDI

SURFACE PREPARATION

The starter roll must be applied to a clean, dry, smooth and dust-free surface.

No special tools are required to install this self-adhering roll starter.



Asphalt Roofing
Manufacturers Association



Product qualified for use as a component of a FORTIFIED Roof™. Additional requirements, eligibility criteria and restrictions apply. For details, visit FORTIFIEDHome.org.

